



Used as a team, the Econ-O-Wash top-load washer and the Econ-O-Dry singleload or stacked dryer effectively clean and dry smaller loads quickly and efficiently—improving on-premise laundry productivity.

GWNMN2

JDE807

JDG809

JSE807

JSG809

**CONTINENTAL**  
GIRBAU®

## ECON-O-WASH TOP-LOAD WASHERS

### AFFORDABLE EFFICIENCY

#### DURABILITY

The Econ-O-Wash topload is constructed for unmatched longevity. It features a durable porcelain enamel washtub, a scratch-resistant, hard-baked porcelain enamel top and lid, a heavy-duty, two-speed motor, and a corrosion-resistant polypropylene pump—all wrapped up in a rugged galvanized steel cabinet!

#### ENERGY EFFICIENCY & HIGH SPIN SPEED

Unlike most home-style top-load washers, which guzzle around 40 gallons of water per load, The Econ-O-Wash topload is engineered with a water saving feature that uses just 27.3 gallons per load! By using less water, on-premise laundries significantly cut hot water consumption—saving energy and lowering utility costs! Moreover, the washer delivers 710 RPM spin speeds to remove more water from every load. In doing so, dry time is reduced—increasing productivity and reducing utility costs! The Econ-O-Wash topload offers superior energy efficiency. At start-up the machine draws fewer amps—conserving additional electricity. No wonder this washer conforms to the Department of Energy (DOE) 2013 efficiency standards.

#### QUALITY OF THE WASH

Superior engineering means laundry gets cleaner. The Econ-O-Wash topload features a curved, four-vane polypropylene agitator with a 210 degree agitator stroke—the longest in the industry. The machine's lengthy stroke delivers increased wash action thereby generating superb wash results.

#### AUTOMATIC BALANCE SYSTEM

Designed to automatically adjust out-of-balance loads, Econ-O-Wash completes wash cycles quietly, smoothly and without interruption. The liquid-filled balance ring at the top of the tub and the washer's advanced suspension design combine to eliminate interrupted wash cycles due to out-of-balance loads. The feature also eliminates the need for an out-of-balance switch!

#### USER-FRIENDLY CONTROL

Econ-O-Wash makes it easy for laundry room attendants to select from several wash cycles. The user simply chooses a cycle—normal, permanent press, delicate, or one of three unique energy-saving cycles—and presses start. It offers three water temperature options for the wash cycle—hot, warm and cold—along with an indicator light that illuminates when the machine is in use.



Four Vane Agitator



Automatic Balance System



Heavy-Duty Drain Hose



User-Friendly Control

#### ECON-O-WASH TOP-LOAD WASHER

- 710 RPM spin speed
- Three water- and energy-saving cycle options
- Scratch-resistant, hard-baked porcelain enamel top and lid
- Automatic balance system
- Durable porcelain enamel washtub
- 100% front serviceability
- Rear self-leveling legs
- Galvanized steel cabinet
- Heavy-duty, two-speed motor



## ECON-O-DRY SINGLELOAD AND STACKED DOUBLELOAD UNMATCHED DURABILITY

*A perfect match to Econ-O-Wash top-load washers, Econ-O-Dry dryers – in single-load or stacked doubleload capacity – are not only easy to use, they dry laundry incredibly fast!*

### ROBUST DOOR AND CYLINDER

Equipped with an oversized door opening, Econ-O-Dry dryers make loading and unloading a snap using a sensible ergonomic design. The robust cylinder capacity takes on larger loads of laundry and provides improved tumble action through axial airflow technology—moving air more evenly through laundry items to get them dry faster!

### EASY TO SERVICE & MAINTAIN

Designed for minimal maintenance and simplified serviceability, the drying tumbler features a lint filter that's easy to reach and clean, but doesn't get in the way. Moreover, when service is necessary, most components are accessible from the front of the machine. The motor, blower, heating element, gas valve and thermostats are serviceable through a lower front panel without disconnecting the door switch.

### SAVE SPACE—DOUBLE PRODUCTION

By selecting the stack Econ-O-Dry model, on-premise laundries double drying capacity using half the space. The stack model offers two individually operable, single-pocket tumblers in one of the narrowest cabinets available (26.88 inches wide). This allows laundries to maximize space and productivity.

### FLEXIBLE CONTROL

The dryer control offers fabric selection options including delicate, permanent press, no heat and normal, and an indicator light that illuminates when the machine is in use. A convenient timer enables the user to manually select dry time according to load type and size.

### GAS OR ELECTRIC

Econ-O-Dry dryers are available in gas or electric heat—making them the right choice for any on-premise laundry. United Laboratories (UL) listed, Econ-O-Dry is built to last for years of trouble-free operation.



Oversized Door Opening



Easy-to-Use Control



#### ECON-O-DRY SINGLELOAD DRYER

- Oversized door opening
- Extra large cylinder capacity
- Front serviceability
- Easy access front lint filter
- Easy-to-use control
- Gas or electric heat
- Reversible door



#### ECON-O-DRY DOUBLELOAD DRYER

- Double-load capacity
- Front serviceability
- Easy access front lint filter
- Easy-to-use control
- Gas or electric heat
- Reversible doors

		GWNMN2	JDE807 JDG809	JSE807 <sup>STACK</sup> JSG809 <sup>STACK</sup>
DIMENSIONS & WEIGHTS	Cylinder Volume <i>cu ft (dm<sup>3</sup>)</i>	3.26 (92.3)	7.0 (199)	7.0 (199)
	Net Weight <i>lbs (kg)</i>	190 (86)		
	Crated Weight <i>lbs (kg)</i>	210 (95)		
	Machine Width <i>inch (mm)</i>	25.63 (651)		
	Machine Depth <i>inch (mm)</i>	28 (711)		
	Machine Height <i>inch (mm)</i>	43 (1092)		
	Floor to Work Surface <i>inch (mm)</i>	36 (914)		
	Shipping Dimensions <i>inch (mm)</i> (WxDxH)	28 x 30 x 45 (711 x 762 x 1143)		
	Available Colors	white		
	Water Consumption <i>gal (l)</i>	27.3 (103.3)		
GENERAL	Hot Water Consumption <i>gal (l)</i>	2.3 (27.3)		
	Modified Energy Factor (MEF)	1.65		
	Water Consumption Factor (WCF)	8.4		
	Washing Speed			
	High Speed <i>strokes per min</i>	67		
	Low Speed <i>strokes per min</i>	44		
	Spin Speed 2-speed			
	High Speed <i>rpm</i>	710		
	Low Speed <i>rpm</i>	473		
	Drain Diameter <i>inch (mm)</i>	1-1/2 (38.1)		
CONNECTIONS	Water Inlets <i>inch (mm)</i>	3/4 (19)		
	Recommended Water Pressure <i>PSI (bar)</i>	20-120 (1.4/8.3)		
	Water Flow <i>gal/min (l/min)</i>	37.5 (140)		
	Motor Power <i>Hp</i>	1/2		
	Amp Protection <i>Amp</i>			
	120/60/1	15		
	230/50/1	10		
	Basket Volume <i>cu ft (dm<sup>3</sup>)</i>		7.0 (199)	7.0 (199)
	Net Weight			
	Electric <i>lbs (kg)</i>		135 (61)	265 (120)
DIMENSIONS & WEIGHTS	Gas <i>lbs (kg)</i>		140 (64)	275 (125)
	Crated Weight <i>lbs (kg)</i>			
	Electric <i>lbs (kg)</i>		145 (66)	280 (127)
	Gas <i>lbs (kg)</i>		150 (68)	290 (132)
	Machine Width <i>inch (mm)</i>		26.88 (683)	26.88 (683)
	Machine Depth <i>inch (mm)</i>		28 (711)	28 (711)
	Machine Height <i>inch (mm)</i>		43 (1092)	76.63 (1946)
	Door Opening <i>inch (mm)</i>		24.7 (628)	24.7 (628) per basket
	Shipping Dimensions <i>inch (mm)</i> (WxDxH)		29.5 x 30.5 x 45 (749 x 775 x 1143)	30 x 33 x 80 (762 x 838 x 2032)
	Available Colors		white	white
CONNECTIONS	Exhaust Diameter <i>inch (mm)</i>		4 (102)	4 (102)
	Exhaust Air Flow <i>cfm (m<sup>3</sup>/min)</i>		220 (6.23)	220 (6.23) per basket
	Basket Motor Power <i>Hp</i>		1/3	1/3 per basket
	Gas Heating <i>BTU/h (Kcal/h)</i>		25,000 (6300)	25,000 (6300) per basket
	Gas Inlet Diameter <i>inch</i>		3/8 N.P.T.	3/8 N.P.T.
	Heating Element Wattage			
	60Hz – 208 Volt* *		4750	4750
	240 Volt		5350	5350
	50Hz – 230 Volt		4800	4800
	Amp Protection <i>Amp</i>			
CONNECTIONS	Gas			
	120/60/1		15	15 per basket
	230/50/1		10	10 per basket
	Electric 120/240/60/1		30	30 per basket
CONNECTIONS	230/50/1		30	30 per basket



\* Product design and specifications are subject to change without notice. For the most current and complete technical specifications, architectural line drawings and warranty information, please visit our website at [www.continentalgirbau.com](http://www.continentalgirbau.com).

\*\* Conversion kit required for 208 volt models. Contact Continental Girbau Inc. or your local authorized Continental distributor for details.

**CONTINENTALCARE™**  
 BUY WITH COMPLETE CONFIDENCE | 3-YR LIMITED PARTS WARRANTY  
 5-YR KEY COMPONENT WARRANTY

DISTRIBUTED BY:



**[www.continentalgirbau.com](http://www.continentalgirbau.com) • 800-256-1073**  
 2500 State Road 44 • Oshkosh, WI 54904 • 920-231-8222 • Fax 920-231-4666